

GENERAL			
	D3S 42V 35W PK32d-5	Features	original equipment manufacturer quality, high luminance, bright white light, color temperature up to 4300K, quartzglass, UV-cut, mercury-free
	Ordering Number 24021	Standard	ECE R99 DOT
Product Description	HID lamp	Typical Applications	low beam, high beam, aircraft exterior light

TECHNICAL DETAILS			
 <p>COMING SOON</p>		Rated Voltage	ECE R99: 42V
		Rated Wattage	35W ± 3W @42V
		Base	PK32d-5
		Operating Conditions	burning position: horizontal, maximum operating temperature pinch: Maximum Operating
		Luminous Flux	3200 lm ± 450 lm @42V
Geometry	Light center length: 27,1mm Bulb diameter: max. 10mm	Lifetime	B3: 2000h @13,5V Tc: 4000h @13,5V

DELIVERY DETAILS		
Packaging	Commercial Box Packaging: 12pcs. (12×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. The lamp can only be used in conjunction with a electronic starter.

valid from 12/04/2017

replace for 03.03.2015-V1-PN15/0122

file 24021 - D3S 42V 35W PK32d-5.100

Disclaimer:
 Subject to change without notice. Errors and omission accepted.
 Always make sure to use the most recent release.

vosla GmbH Plauen Germany
www.vosla.com