

GENERAL			
	<b>D4R</b> 42V 35W P32d-6	<b>Features</b>	original equipment manufacturer quality, high luminance, bright white light, color temperature up to 4300K, quartzglass, UV-cut, mercury-free
	<b>Ordering Number</b> 24036	<b>Standard</b>	ECE R99 DOT
<b>Product Description</b>	HID lamp	<b>Typical Applications</b>	low beam, high beam, aircraft exterior light

TECHNICAL DETAILS			
  COMING SOON	<b>Rated Voltage</b>	ECE R99: 42V	
	<b>Rated Wattage</b>	35W ± 3W @42V	
	<b>Base</b>	P32d-6	
	<b>Operating Conditions</b>	maximum operating temperature pinch: Maximum Operating Temperature: max. 350°C pinch	
	<b>Luminous Flux</b>	2800 lm ± 450 lm @42V	
	<b>Geometry</b>	Light center length: 27,1mm Bulb diameter: max. 10mm	<b>Lifetime</b>

DELIVERY DETAILS		
<b>Packaging</b>	Commercial Box Packaging: 32pcs. (32×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. The lamp can only be used in conjunction with a electronic ballast and starter.