



GENERAL

	HIR2 L 12V 55W PX22d 9012 L 12,8V 60W PX22d Long Lifetime	Features	original equipment manufacturer quality, Infrared coating, yellow cover plate, hardglass, UV-cut
	Ordering Number 27032	Standard	ECE R37 DOT
Product Description	halogen headlighting lamp	Typical Applications	low beam, high beam, Bi-halogen function

TECHNICAL DETAILS

	Geometry Light center length: 28,7mm ± 0,35mm (ECE), 31,5mm ± 0,2mm (DOT) Bulb diameter: max. 12,5mm	Rated Voltage	ECE R37: 12V DOT: 12,8V
		Rated Wattage	max. 63W @ 13,2V max. 60W @ 12,8V
		Base	PX22d
		Operating Conditions	burning position: horizontal, long electrode above filament
		Luminous Flux	1875 lm ± 15% @ 13,2V 1700 lm ± 15% @ 12,8V
		Lifetime	B3: 900h @ 13,2V B3: 600h @ 14,0V B10: 680h @ 14,0V Tc: 1300h @ 13,2V Tc: 830h @ 14,0V

DELIVERY DETAILS

Packaging	Industrial Packaging: 200pcs. (5×40) Commercial Box Packaging: 100pcs. (10×10×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.
------------------	---	---

valid from 07.12.2017

replace for 12.04.2017

file 27032 - HIR2 L 12V 55W PX22d.100

Disclaimer:
 Subject to change without notice. Errors and omission accepted.
 Always make sure to use the most recent release.