

Product Information Sheet H11 +120 12V

GENERAL				
	H11 +120 12V 55W PGJ19-2 +120 More Light		Features	original equipment manufacturer quality, high luminance, silver top color, green cover plate, hardglass, UV-cut
	Ordering Number 27478		Standard	ECE R37 DOT
Product Description	halogen headlighting lamp		Typical Applications	low beam, fog light
TECHNICAL DETAILS				
	-Bezugsachse reference axis		Rated Voltage	ECE R37: 12V
	Bezugsebene Merence plane	Rated Wattage	max. 62W @13,2V max. 59W @12,8V	
10,2		Base	PGJ19-2	
			Operating Conditions	burning position: horizontal, long electrode above filament
			Luminous Flux	1350 lm ± 10% @13,2V 1250 lm ± 150lm @12,8V
Geometry	Light center length: 25mm ± 0,2mm Bulb diameter: max. 12,5mm		Lifetime	B3: 200h @13,2V Tc: 400h @13,2V
DELIVERY DETAILS				
Packaging	Industrial Packaging: 140pcs. (4×35) Commercial Box Packaging: 100pcs. (10×10×1)		Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.	
valid from 12.04.2018	replace for 07.12.20	017	file	27478 - H11 +120 12V 55W PGJ19-2.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com