

Product Information Sheet HB5

GENERAL					
	HB5 9007 12V 65W/55W PX29t	Features	original equipment manufacturer quality, black top color, hardglass		
	Ordering Number 28007	Standard	DOT		
Product Description	halogen headlighting lamp	Typical Applications	low beam, high beam		

TECHNICAL DETAILS

	max.Ø17 Igsachse	Rated Voltage	DOT: 12V		
Bezugsebene reference plane		Rated Wattage	max. 70W/60W @12,8V		
		Base	PX29t		
		Operating Conditions	burning position: horizontal		
		Luminous Flux	1350/1000 lm ± 15% @12,8V		
Geometry	Light center length: 44,5mm Bulb diameter: max. 17mm	Lifetime	B3: 130/380h @14,0V B50: 320/650h @14,0V Tc: 340/680h @14,0V		
DELIVERY DETAILS					
Packaging	Industrial Packaging: 200pcs. (8×25) Commercial Box Packaging: 100pcs. (10×10×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.			

valid from 12/04/2017 replace for

19.02.2013-V1-PN12/0248

file 28007 - 9007 12V 65W/55W PX29t.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com