

Product Information Sheet H1 BLUE 12V

| GENERAL | | | | |
|---------------------|---|----------------------|--|--|
| | H1 BLUE 12V 55W P14,5s Blue Version | Features | original equipment manufacturer quality, bright white light, blue coating, color temperature up to 4000K, quarzglass, UV-cut | |
| | Ordering Number 28630 | Standard | ECE R37 DOT | |
| Product Description | halogen headlighting lamp | Typical Applications | low beam, high beam, fog light | |

TECHNICAL DETAILS

| € 8,5 max. 18,2 max. 38,5 max. 18,2 max. 19,2 max. 10,2 max | | Rated Voltage | ECE R37: 12V | |
|--|---|---|---|--|
| | | Rated Wattage | max. 68W @13,2V | |
| | | Base | P14,5s | |
| | | Operating Conditions | burning position: horizontal, long electrode above filament | |
| | | Luminous Flux | 1550 lm ± 15% @13,2V | |
| Geometry | Light center length: 25mm ± 0,25mm Bulb diameter: max. 8,5mm | Lifetime | B3: 150h @13,2V Tc: 250h @13,2V | |
| DELIVERY DETAILS | | | | |
| Packaging | Industrial Packaging: 320pcs. (4×80) Commercial Box Packaging: 100pcs. (10×10×1) | Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. | | |

valid from 12/04/2017 replace for

14.11.2014-V-PN14/0499

file 28630 - H1 BLUE 12V 55W P14,5s.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com