

Product Information Sheet H11 24V

GENERAL			
	H11 24V 70W PGJ19-2	Features	original equipment manufacturer quality, black top color, green cover plate, hardglass, UV-cut
	Ordering Number 28778	Standard	ECE R37
Product Description	halogen headlighting lamp with double coil	Typical Applications	low beam, fog light
TECHNICAL DETAILS			
	-Bezugsachse — reference axis	Rated Voltage	ECE R37: 24V
	Bezugsebene ference plane	Rated Wattage	max. 80W @28V
		Base	PGJ19-2
		Operating Conditions	burning position: horizontal, long electrode above filament
		Luminous Flux	1600 lm ± 10% @28V
Geometry	Light center length: 25mm ± 0,25mm Bulb diameter: max. 12,5mm	Lifetime	B3: 500h @28V Tc: 1000h @28V
DELIVERY DETAILS			
Packaging	Industrial Packaging: 140pcs. (4×35) Commercial Box Packaging: 100pcs. (10×10×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.	
valid from 25.10.2017	replace for 12/04/201	7 file	28778 - H11 24V 70W PGJ19-2.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com