

Product Information Sheet H4 12V

GENERAL				
	H4 12V 60W/55W P43t	Features	original equipment manufacturer quality, black top color, hardglass, UV-cut	
	Ordering Number 28881	Standard	ECE R37 DOT	
Product Description	halogen headlighting lamp	Typical Applications	low beam, high beam	
TECHNICAL DETAILS				
reference axis		Rated Voltage	ECE R37: 12V	

TECHNICAL DETAILS			
reference axis reference plane			

Light center length: 28,5mm +0,35mm/-0,25mm Bulb diameter: max. 17mm

Rated Voltage	ECE R37: 12V	
Rated Wattage	max. 75W/68W @13,2V	
Base	P43t	
Operating Conditions	burning position: horizontal	
Luminous Flux	1650/1000 lm ± 15% @13,2V	
Lifetime	B3: 240/400h @13,2V Tc: 500/900h @13,2V	

DELIVERY DETAILS

Packaging

Geometry

Industrial Packaging: 200pcs. (5×40) Commercial Box Packaging: 100pcs. (10×10×1) Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.

valid from 12/04/2017 replace for 07.05.2014-V2-PN14/0233 file 28881 - H4 12V 60W/55W P43t.100