

#### GENERAL

|   |  |                             |                               |
|---|--|-----------------------------|-------------------------------|
|  | <b>T4W SHP</b><br>24V 4W BA9s<br>Shock Proof               | <b>Features</b>             | softglass, support wire       |
|   | <b>Ordering Number</b><br>37143                            | <b>Standard</b>             | ECE R37                       |
| <b>Product Description</b>  | Incandescent signalling and interior lamp with single coil | <b>Typical Applications</b> | parking light, interior light |

#### TECHNICAL DETAILS

|  |  |                                |
|--|--|--------------------------------|
| <br><br>COMING SOON | <b>Rated Voltage</b>   | ECE R37: 24V                   |
|  | <b>Rated Wattage</b>   | max. 5,5W @28V                 |
|  | <b>Base</b>  | BA9s                           |
|  | <b>Operating Conditions</b>  | burning position: horizontal   |
|  | <b>Luminous Flux</b>   | 35 lm ± 20% @28V               |
|  | <b>Lifetime</b>  | B3: 120h @28V<br>Tc: 350h @28V |
| <b>Geometry</b>  | Light center length:<br>15mm ± 1,5mm<br>Bulb diameter:<br>max. 8,8mm |                                |

#### DELIVERY DETAILS

|                  |  |   |
|------------------|--|---|
| <b>Packaging</b> | Commercial Box Packaging:<br>200pcs. (20×10) | Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture.<br>For use in closed luminaires only. |
|------------------|--|---|

valid from 12/04/2017

replace for -

file 37143 - T4W SHP 24V 4W BA9s.100

**Disclaimer:**  
 Subject to change without notice. Errors and omission accepted.  
 Always make sure to use the most recent release.