

| GENERAL | | | |
|---|---|-----------------------------|---------------------------|
|  | R5W SHP 24V 5W BA15s Shock Proof | Features | softglass, support wire |
| | Ordering Number 37186 | Standard | ECE R37 |
| Product Description | Incandescent signalling lamp with double coil | Typical Applications | rear light, parking light |

| TECHNICAL DETAILS | | | |
|--|-----------------|---|------------------------------|
|  <p>COMING SOON</p> | | Rated Voltage | ECE R37: 24V |
| | | Rated Wattage | max. 7,7W @28V |
| | | Base | BA15s |
| | | Operating Conditions | burning position: horizontal |
| | | Luminous Flux | 50 lm ± 20% @28V |
| | Geometry | Light center length: 19mm ± 1,5mm Bulb diameter: max. 19mm | Lifetime |

| DELIVERY DETAILS | | |
|------------------|--|---|
| Packaging | Commercial Box Packaging: 200pcs. (20×10) | Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. |

valid from 24/10/2017

replace for 12/04/2017

file 37186 - R5W SHP 24V 5W BA15s.100

Disclaimer:
 Subject to change without notice. Errors and omission accepted.
 Always make sure to use the most recent release.