



GENERAL			
	D1S 85V 35W PK32d-2	Features	original equipment manufacturer quality, high luminance, bright white light, color temperature up to 4100K, quartzglass, UV-cut
	Ordering Number 24001	Standard	ECE R99 DOT
Product Description	HID lamp	Typical Applications	low beam, high beam, aircraft exterior light

TECHNICAL DETAILS			
 <p>COMING SOON</p>	Rated Voltage	ECE R99: 85V	
	Rated Wattage	35W ± 3W @85V	
	Base	PK32d-2	
	Operating Conditions	burning position: horizontal, maximum operating temperature pinch: Maximum Operating	
	Luminous Flux	3200 lm ± 450 lm @85V	
	Geometry	Light center length: 27,1mm Bulb diameter: 9mm ± 1mm	Lifetime

DELIVERY DETAILS		
Packaging	Commercial Box Packaging: 12pcs. (3x4x1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. The lamp can only be used in conjunction with a electronic starter.

valid from 12/04/2017

replace for 01.07.2014-V1-PN14/0309

file 24001 - D1S 85V 35W PK32d-2.100

Disclaimer:
 Subject to change without notice. Errors and omission accepted.
 Always make sure to use the most recent release.

vosla GmbH Plauen Germany
www.vosla.com