

Product Information Sheet D1R 85V

GENERAL			
	D1R 85V 35W PK32d-3	Features	original equipment manufacturer quality, high luminance, bright white light, color temperature up to 4100K, quarzglass, UV-cut
	Ordering Number 24006	Standard	ECE R99 DOT
Product Description	HID lamp	Typical Applications	low beam, high beam, aircraft exterior light
TECHNICAL DETAILS			
		Rated Voltage	ECE R99: 85V
COMING SOON		Rated Wattage	35W ± 3W @85V
		Base	PK32d-3
		Operating Conditions	maximum operating temperature pinch: Maximum Operating Temperature: max. 350°C pinch
		Luminous Flux	2800 lm ± 450 lm @85V
Geometry	Light center length: 27,1mm Bulb diameter: max. 10mm	Lifetime	B3: 2000h @13,5V Tc: 3000h @13,5V
DELIVERY DETAILS			
Packaging	Commercial Box Packaging: 12pcs. (3×4×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. The lamp can only be used in conjuction with a electronic starter.	

valid from 12/04/2017

replace for

-

file 24006 - D1R 85V 35W PK32d-3.100

Disclaimer: Subject to change without notice. Errors and omission accepted.

Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com