



GENERAL

| | | | |
|---|---------------------------------|-----------------------------|---|
|  | D2R 85V 35W P32d-3 | Features | original equipment manufacturer quality, high luminance, bright white light, color temperature up to 4000K, quartzglass, UV-cut |
| | Ordering Number 24016 | Standard | ECE R99 DOT |
| Product Description | HID lamp | Typical Applications | low beam, high beam, aircraft exterior light |

TECHNICAL DETAILS

| | | | |
|--|---|--|--------------------------------------|
|  <p>COMING SOON</p> | Rated Voltage | ECE R99: 85V | |
| | Rated Wattage | 35W ± 3W @85V | |
| | Base | P32d-3 | |
| | Operating Conditions | burning position: horizontal, maximum operating temperature pinch: Maximum Operating | |
| | Luminous Flux | 2800 lm ± 450 lm @85V | |
| Geometry | Light center length: 27,1mm Bulb diameter: max. 10mm | Lifetime | B3: 2000h @13,5V Tc: 3000h @13,5V |

DELIVERY DETAILS

| | | |
|------------------|---|--|
| Packaging | Commercial Box Packaging: 32pcs. (4x8x1) | Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only. The lamp can only be used in conjunction with a electronic ballast and starter. |
|------------------|---|--|

valid from 12/04/2017

replace for 01.07.2014-V1-PN14/0309

file 24016 - D2R 85V 35W P32d-3.100

Disclaimer:
 Subject to change without notice. Errors and omission accepted.
 Always make sure to use the most recent release.