

Product Information Sheet R10W 24V

GENERAL			
	R10W 24V 10W BA15s	Features	softglass
	Ordering Number 37326	Standard	ECE R37
Product Description	Incandescent signalling lamp with single coil	Typical Applications	rear light, reversing light
TECHNICAL DETAILS			
	ø 19,0 max.	Rated Voltage	ECE R37: 24V
	7,5 max. 30,0 max	Rated Wattage	max. 14W @28V
		Base	BA15s
		Operating Conditions	burning position: horizontal
		Luminous Flux	125 lm ± 20% @28V
Geometry	Light center length: 19mm ± 1,5mm Bulb diameter: max. 19mm	Lifetime	B3: 300h @28V Tc: 800h @28V
DELIVERY DETAILS			
Packaging	Commercial Box Packaging: 200pcs. (20×10)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.	
valid from $12/08/2018$	replace for 24/10/2017	filo	27226 - 21014/ 241/ 1014/ 2415: 100

valid from 13/08/2018

replace for 24/10/2017

file 37326 - R10W 24V 10W BA15s.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com