Product Information Sheet

www.narva-plauen.de



Technical Details

| Railway Signaling | | |
|----------------------------|-------------------------------|--|
| | Type RS6013 17V 0,5A BA22d | |
| | Ordering – No. 46013 | |
| Product Description | Signaling Lamp | |
| Features | Single Filament | |
| Applications | Railway Signal | |

| Drawing (in mm) | | |
|-----------------|----------|-----------|
| Ø 36 max | · - | |
| | 34.0±0.5 | ₹ 28 max. |

| reclifical Details | | |
|---------------------------------|---|--|
| Туре | RS6013 | |
| Rated Voltage (V) | 17 | |
| Wattage (W) (at 0,5A) | max. 8,9 | |
| Luminous Flux (Im) (at 0,5A) | 60 ± 10% | |
| Lumen Maintenance (at 0,5A) | 70% at 2250h | |
| Average Lifetime (h)(at 0,5A) | 3000 | |
| Base | BA22d | |
| Maximum Overall Length (mm) | max. 58,0 | |
| Bulb Diameter (mm) | max. 36,0 | |
| Light Center Length (mm) | 34,0 ± 0,5 | |
| Packaging Configuration | 200 | |
| Environmental Remark | Product don't contain lead or mercury and is conform with Directive 2011/65/EC "Restriction of the use of certain hazardous substances in electrical and electronic equipment". | |



